

1KG PORTABLE FIRE EXTINGUISHER



Certified By



SPECIFICATIONS

Type	Stored Pressure Type
Extinguishant	ABC Dry Powder
Capacity	1kg
Propellant	Nitrogen (N2)
Valve	Controllable Non Ferrous Valve with Pressure Indicator
Body Diameter(mm)	79mm
Overall Height(mm)	325mm
Approx. Full Weight	1.7kg
Working Temp. Range	-20°C to +60°C
Working Pressure	12 BAR
Test Pressure	25 BAR
Burst Pressure	Exceeds 69 BAR
Approx. Discharge Range	2m - 3m
Approx. Discharge Time	9 sec
Fire Rating	5A/21B
Fire Class	A, B, C +Electrical
Internal Coating	Stoving Epoxy Primer
Paint Finishing	RAL 3000 Red Epoxy Polyester Powder Coating
Manufactured & Certified to	MS 1539 : Part 1 : 2002

PRODUCT ADVANTAGES

1. Light & Portable
2. Easy to use
3. Easy to maintain
4. Suitable for house, office or car
5. No costly servicing
6. 10 years lifespan

HOW TO USE A FIRE EXTINGUISHER



Pull the pin
in the handle



Aim the nozzle
at the base of the fire



Squeeze the
lever slowly



Sweep from
side to side

