## **PHOTOELECTRIC SMOKE ALARM (WP30)**

"EN14604 Standard"





#### **SPECIFICATIONS**

Model No. WP-30 Product lifespan 10 years

Operating voltage 3V lithium battery

Static current 8uA 35mA Alarm current

Alarm output Sound & Flash alarm

Sound level 85dB/3m

Installation method Ceiling mounted Sensitivity 1.8%ft±0.8%ft

Working environment -10°C~+50°C,(≤95%RH No congelation)

**Dimension** 95\*41mm

#### **PRODUCT ADVANTAGES**

- 1. Built-in 3V lithium battery, 10 years lifetime.
- 2. Photoelectric sensitive sensor.
- 3. Buzzer, over 85db alarm sound.
- 4. Red LED, LED flashes every 53 seconds in monitoring status and flashes quickly when alarms.
- 5. Test/hush button, test the normal operation and the hush function.

#### **SENSITIVE & INTELLIGENT**

360° perception of smoke with fewer noise alarms



# PHOTOELECTRIC SMOKE ALARM (WP30)

"EN14604 Standard"







Operated by upgraded 3v lithium battery with 10-years lifespan, constant power supply

# 2 Smoke Detection in All Directions




Stand-alone photoelectric sensor detect smoke in all directions.

#### **3** Loud Alarm Sound



Built-in buzzer- The LED light with flash and sensor will alarm with more than 80dB sound, once it detects smoke or fire.

#### Self-checking Prompt






# 5 Environment-friendly ABS Shell



Fire-proof ABS cases with high temperature resistance and corrosion protection.

## 6 Easy for Installation






### Dust-proof Design



Tiny nozzle only for smoke, and prevent from dust to keep its high sensitivity.

#### 8 Anti-drop Design





#### **Application**

Factory, Warehouse, Hotel, Shopping Mall, Home, Hospital, School, Office

